

Frontier™ 5000 Rotors

Offering Flexibility to Maximize Sample Preparation

- Choose from a range of rotors to be used with Frontier centrifuges to match capacities and flexibility required for your basic to high-performance sample preparation needs.
- Designed with usability in mind, the Frontier rotors can be effortlessly installed or removed in a few quick and simple steps, and users have easy access to the samples.
- The sturdy rotors are constructed of high-quality materials, built to last through demanding workflows from autoclave sterilization to sub-zero temperature.



Application Centrifugation Accessory

Construction Aluminum or polypropylene material

Model	Rotor Style	Capacity	Max g-force	Maximum Speed	Item Number
R-A8 × 2/6M	Angle	8 × 1.5 / 2.0 ml	2,560 g	6,000 rpm	30129559
R-A4 × PCR/6		4 × 0.2 ml PCR8	2,260 g		30129560
R-A24 × 2/15M		24 × 1.5 / 2.0 ml	21,953 g	15,200 rpm	30130870
R-A24 × 2/15MS					30130871
R-A30 × 2/13MS		30 × 1.5 / 2.0 ml	19,150 g	13,500 rpm	30130872
R-A12 × 5/14MS		12 × 5 ml	19,978 g	14,500 rpm	30130873
R-A4 × PCR/15		4 × 0.2 ml PCR8	15,342 g	15,000 rpm	30130874
R-A12 × 15/6M		12 × 15 ml	4,427 g	6,000 rpm	30130877
R-A6 × 50/6M		7 × 50 ml			30130878
R-A44 × 2/13M		44 × 1.5 / 2.0 ml	17,317 g	13,500 rpm	30130879
R-S6 × 5/4	Swing out	6 × 5 ml	1,817 g	4,000 rpm	30130880
R-A24 × CAP/12	Angle	24 × Capillaries	14,970 g	12,000 rpm	30130881
R-A24 × 2/16MIS		24 × 1.5 / 2.0 ml	24,325 g	16,000 rpm	30304361
R-S4 × 250/4MI	Swing out	4 × 250 ml	3,780 g	4,500 rpm	30314820
R-A6 × 250/8MI	Angle	6 × 250 ml	10,016 g	8,000 rpm	30314821
R-S4 × 100/4MI	Swing out	4 × 100 ml	3,350 g	4,500 rpm	30314822
R-S4 × 100/5MIS			3,885 g	5,000 rpm	30314823
R-S6 × MTP/4MI		2 × 3 MTP	2,716 g	4,500 rpm	30314824
R-A6 × 85/14MI	Angle	6 × 85 ml	20,984 g	13,500 rpm	30314825
R-A6 × 85/13MI			21,726 g	13,000 rpm	30314826
R-A4 × 85/12MI		4 × 85 ml	14,809 g	12,000 rpm	30314827
R-S16 × 50/4MI	Swing out	16 × 50 ml	3,735 g	4,500 rpm	30314828
R-A10 × 50/10MI	Angle	10 × 50 ml	16,022 g	10,500 rpm	30314829
R-A6 × 50/6MI		7 × 50 ml	4,427 g	6,000 rpm	30314830
R-A6 × 50/13MI			15,869 g	13,000 rpm	30314831
R-A30 × 15/4MI		30 × 15 ml	2,830 g	4,500 rpm	30314832
R-A20 × 10/12MI		20 × 10 ml	15,775 g	12,000 rpm	30314833
R-A12 × 15/6MI		12 × 15 ml	4,427 g	6,000 rpm	30314834
R-A44 × 2/16MI		44 × 1.5 / 2.0 ml	24,039 g	16,000 rpm	30314835
R-A30 × 2/14MIS		30 × 1.5 / 2.0 ml	20,595 g	14,000 rpm	30314836
R-A24 × 2/16MI		24 × 1.5 / 2.0 ml	24,325 g	16,000 rpm	30314838
R-A12 × 2/18MI		12 × 1.5 / 2.0 ml	23,542 g	18,000 rpm	30314839
R-A64 × 0.5/13I		64 × 0.5 ml	16,298 g	13,500 rpm	30314840
R-A4 × PCR/15I		4 × 8-w PCR Strip	15,343 g	15,000 rpm	30314841